



工程指示 / 要求簡箋(E.I.)

工程指示編號：EI 6255/16 修改版次：
 工程編號：J835 工程名稱：將軍澳天晉中心
 工程項目：百叶 - 確認不銹鋼 訂購
 收件人：羅小姐 發件人：Eddie 日期：2016-11-15

要求提供 / 確認 事項：

- | | | |
|--|-------------------------------------|-------------------------------|
| <input type="checkbox"/> 初步鋁料 B.M. | <input type="checkbox"/> 加工折圖，然後生產 | <input type="checkbox"/> 尺寸表 |
| <input type="checkbox"/> 正式鋁料 B.M. | <input type="checkbox"/> 技術上資料 / 指示 | <input type="checkbox"/> 報價 |
| <input type="checkbox"/> 配件 B.M. | <input type="checkbox"/> 樣辦或貨品說明書 | <input type="checkbox"/> 分判合約 |
| <input checked="" type="checkbox"/> 其他：_____ | | |

內容：

~~316~~ 不銹鋼網 5% J
 網網尺寸 = 10x10x2 mm dia

請在 2016-11-29 前完成上列要求。

附有關圖紙 / 文件：

1+

以上項目為：

- 原合約工程包 原合約工程加 / 減賬 新工程報價

原因：-

分發東莞各部門：

- () 生產技術總監 連附件 () 技術部 連附件 () 生產部 連附件 () 機械設計部 連附件
 () 採購部 連附件 () 生產統籌部 連附件
 () 質檢部 連附件 () 會計部 連附件 () 報關組 連附件 () 其他 _____ 連附件

分發香港各部門：

- () 行政部 連附件 () 會計部 連附件 () 統籌部 連附件 () 工程部地盤科文 連附件
 () 採購部 連附件 () QS 部 連附件 () 維修部 連附件 () 其他 _____ 連附件

傳遞編號：

HK 2866 (FTP)

發件人簽署：

項目經理簽署：

Design, Supply & Installation of Curtain Wall, Glass Wall, Glass Canopy and Aluminium Works to Podium
 For Tseung Kwan O Area 66D2, TKOTL118, N.T. (Tender Ref. No. P160251)
 Material Specification

ITEM	DESCRIPTION	REQUIREMENT	Midi
Aluminium			
1	Origin		PRC
2	Supplier (Extrusion)		Panasia
3	Fluorocarbon Coating		
3.1	Fluorocarbon Coating	'Duranar PPG' PVF2	'Duranar PPG' PVF2
3.2	Fluorocarbon Coating Thickness	3-Coat (40 micron)	3-Coat (40 micron)
3.3	Fabrication Factory (Fluorocarbon Coating)		Panasia
3.4	Fluorocarbon Coating Colour :	(all subject to the Architect's approval) UC50598XL Silver Grey	(all subject to the Architect's approval) UC50598XL Silver Grey
4	Aluminium Window Section Wall Thickness (mm):	2.3mm min.	2.3mm min.
5	Glass Wall Section Wall Thickness (mm):	3mm thk. min.	3mm thk. min.
6	Curtain Wall Section Wall Thickness (mm):	3mm thk. min.	3mm thk. min.
7	Aluminium Thickness		
7.1	All unless specified	3mm thk. min.	3mm thk. min.
8	Fabrication Factory Name		Midi
9	Fabrication Factory Self-owned / Outside Factory		Self-owned

Glass			
1	Origin of Glass	PRC	PRC
2	Brand of Glass	三鑫	信義
3	Fabrication Factory		三鑫
4.1	Tempered	8mm clear tempered glass (min.)	8mm clear tempered glass (min.)
4.2	Tempered	10mm clear tempered glass (min.)	10mm clear tempered glass (min.)
4.3	Tempered	12mm monolithic clear tempered glass (min.)	12mm monolithic clear tempered glass (min.)
4.4	Tempered	12mm monolithic clear tempered glass (min.) C.O.P	12mm monolithic clear tempered glass (min.) C.O.P
4.5	Tempered	15mm monolithic clear tempered glass (min.)	15mm monolithic clear tempered glass (min.)
4.6	Tempered	15mm monolithic clear tempered glass (min.) C.O.P	15mm monolithic clear tempered glass (min.) C.O.P
4.7	Laminated	10mm clear tempered + 1.52PVB + 10mm clear tempered glass (min.)	10mm clear tempered + 1.52PVB + 10mm clear tempered glass (min.)
4.8	Laminated	12mm clear tempered + 1.52PVB + 12mm clear tempered glass (min.)	12mm clear tempered + 1.52PVB + 12mm clear tempered glass (min.)
4.9	Laminated	19mm clear tempered + 1.52PVB + 19mm clear tempered glass (min.)	19mm clear tempered + 1.52PVB + 19mm clear tempered glass (min.)
4.10	Glass Fins	19mm monolithic clear tempered glass (min.)	19mm monolithic clear tempered glass (min.)
5	Shading Coefficient (S.C.)	0.97 max.	0.97 max.
6	Design Wind Load (min. Kpa)	According to H.K. Wind Code	According to H.K. Wind Code
7	All Tempered Glass should be 100% Heat Soak Tested according to PNAP APP-37 & EN14179	Yes	Yes
8	All Tin Side of Glass Should Face Inwards / Indoor	Yes	Yes

Others			
1	Anchor Bolt	Hilti HST-R or Fischer Grade 316	Hilti HST-R or Fischer Grade 316
2	Self tapping s.s. rivet and screw (if any)	Piasta/ J.A.M/ Orca Bolts A4 Grade 316	Orca Bolts A4 Grade 316
3	Stainless Steel Members (exposed / wet zone)	Grade 316	Grade 316
4	Steel	Grade S275 (BS EN 10025) and hot dip galvanized	Grade S275 (BS EN 10025) and hot dip galvanized
5	S.S. Cladding	1.5mm thk. min. grade 316 hairline finish	1.5mm thk. min. grade 316 hairline finish
6	S/S Wire Mesh Eye (Grade 316), if any	10x10x2mm dia.	10x10x2mm dia.
7	Waterproofing for Grouting	籃圈仔	籃圈仔
8	Waterproofing coating	Masterseal 540	Masterseal 540

此 R 子